



Features

- > Extremely small SMD type crystal units.
- > High precision and high frequency stability.
- > Excellent heat resistance and environmental characteristics.
- > Applications in PDA, DSC, DVC, PC, etc.
- > RoHS Compliant / Pb Free.

Electrical Specifications

Frequency Range	24.000 ~ 54 MHz
Load Capacitance	Series, 6~32 pF, or specify
Frequency Tolerance (at 25 °C)	±10, ±20, ±30 ppm, or specify
Frequency Stability Over Operating Temperature Range	±10, ±20, ±30 ppm, or specify
Operating Temperature Range	-20 ~ +70 °C, -40~+85 °C, or specify
Storage Temperature Range	-40 ~ +85 °C
Shunt Capacitance (C0)	7 pF Max.
Drive Level	1 ~ 1000 µW (100 µW typical)
Insulation Resistance	500 MΩ Minimum at 100VDC
Aging (at 25°C)	±3 ppm / year Max.

Equivalent Series Resistance(ESR)

Frequency Range (MHz)	Mode	ESRΩ(MAX)
24.000~25.999	FOUN	100
26.000~29.999	FOUN	80
30.000~54.000	FOUN	60

Frequency Stability Over Operating Temperature Range

Temperature Range	Frequency Stability (ppm)			
	±10	±15	±20	±30
0 ~ +50°C	*	*	*	*
-10 ~ +60°C	*	*	*	*
-20 ~ +70°C	*	*	*	*
-30 ~ +80°C		*	*	*
-40 ~ +85°C			*	*

Dimensions

